

HRL-800R

The Entry-level and Practical Rotary Laser

- The laser module of HRL800R will rotate freely to form a laser scanning surface , It could provide high precision leveling service.



Data Specifications

PERFORMANCE

Leveling Accuracy	±3mm at 30m (±1/8 in at 100ft)
Leveling Range	±5°
Working Range with Receiver Diameter	600m
Visible Working Range	40m
Spinning Speed	0, 60, 120, 300, 600 r.p.m
Directional-Scanning Angle	0°, 10°, 45°, 90°, 180°
Slope-adjusting Range	±5° (Bi-directional)
Light Source	Laser Diode
Wavelength	635-650nm
Remote Control Distance	Approximately 30m
Power Supply	DC4.8-6V (4 Section of NI-MH Rechargeable Battery) / 4-Cell Alk-battery
Operational Approximately	30 hours
Environmental Protection	IP54
Dimension	160mm x 160mm x 185mm
Weight	2.0kg
Remote Working Range	Min.15m
Working Temperature	0°C - 50°C

Descriptions and specifications are subject to change without notice.



Hi-Target AUTHORIZED DISTRIBUTION PARTNER

19J318

Hi-Target Surveying Instrument Co., Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555, the North of Panyu RD, Panyu District, 511400 Guangzhou, China.
TEL: +86-20-28688296 E-mail: info@hi-target.com.cn www.hi-target.com.cn