


HT-32 Auto Level



HT-32

OVERVIEW



Featuring a lightweight and easy-to-grasp compact design, the HT-32 is an air damping compensator auto level that provides durability and flexibility for your surveying needs. Even when fine vibrations are present, rest assured that this equipment provides accurate and precise results. The HT-32 has an eco-friendly frame that is reinforced with IP66 protection to endure harsh weather conditions.

KEY FEATURES





Rugged, durable and accurate



32x Magnification



X-style air dumping compensator



IP66



SPECIFICATIONS

Standard deviation for 1 km double levelling		1.0mm
Telescope	Magnification	32X
	Filed of View	1°20'
	Objective Aperture	38mm
	Minimum Focusing Distance	1m
	Stadia	100
Compensator	Туре	X-style Air Dumping
	Compensating Range	±15′
	Setting Accuracy	±0.5"
Environmental conditions	Operating Temperature	-20°C ~+50°C
	Storage Temperature	-40°C ~+70°C
	Protection Level	IP66
	Net Weight	1.4KG





AUTHORIZED DISTRIBUTION PARTNER

20N102

Hi-Target Surveying Instrument Co. Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555, North of Panyu RD, Panyu District, 511400 Guangzhou, China. www.hi-target.com.cn +86-20-28688296 info@hi-target.com.cn