

# HTS-720

Android Total Station



IP65

# HTS-720

## Android Total Station



Android 9.0



5.5 inch touch screen



EDM 1000m



Wireless Connection



8MP Camera



Type-C



Qualcomm CPU



2GB RAM, 16GB ROM

HTS-720 features a 5.5-inch touch high-definition large screen, powered by the Android operating system and our brand-new Android measurement software. With the addition of a built-in camera, measuring and stakeout tasks have never been easier.

## Intuitive T-Survey software

- Quick settings without switching back and forth between pages. Fast, simple, and convenient operation.
- Comprehensive functions specifically designed for different measurement scenarios.
- Supporting updating to the latest version online.



### Road, Bridge and Tunnel measurement

Featuring road, bridge and tunnel design functions, the powerful data processing capabilities of the latest Android measurement software speed up the measurement process and make fieldwork more efficient.



### Calculate height of instrument automatically

Automatic height calculation promises higher accuracy.



### Imaging for recording points

HD photography for drawing up drafts accurately and quickly.



### Graphical electronic bubbles guidance

Animated instruction simplifies the setup process, adjusting the foot screw and leveling the instrument in one step, no more struggling in rotating the instrument back and forth.






## Function

### Visual Stakeout


Reducing frequencies of staring at the telescope and finding points easily through the image guidance, which is accessible to both experienced and novices.




### CAD Stakeout

Enabling millisecond-level dynamic response, the high-performance CAD engine makes selecting stakeout points and lines in one click possible, and makes stakeout more intuitive.

## Application




Bridge



Construction



Mining



Tunnel



Railway



Road

## SPECIFICATIONS

<b>Angle Measurement</b>	
Angle Measuring Principle	Absolute Encoding
Minimum Readout	0.1"
Accuracy	1"/2"(Optional)
<b>Telescope</b>	
Magnification	30X
Field of View	1°30'
Minimum Focusing Distance	1.5 m
Reticle	Illuminated
<b>Compensation</b>	
System	Dual-axis
Working Range	±6'
Accuracy	1"
<b>Distance Measurement (Prism Mode)</b>	
Single Prism <sup>1</sup> (General / Good Atmosphere)	5000 m / 6000 m
Accuracy (Fine / Quick / Tracking)	2 mm+2 ppm
Measuring Time <sup>3</sup> (Repeat / Tracking)	0.5 s / 0.3 s
<b>Reflectorless</b>	
Range <sup>2</sup> (The target is Kodak white board with reflect rate 90%)	1000 m
Accuracy (Change according to the different reflector condition)	3 mm+2 ppm
Measuring Time <sup>3</sup> (Repeat / Tracking)	Approx. 1s
<b>Communication</b>	
Interface	Type-C(OTG), TF Card, RS232
WLAN	2.4 GHz Dual-Band, Support AP mode
Bluetooth	BT2.1+EDR / 3.0 / 4.2 LE
Microphone / Speaker	Available
<b>System Configuration</b>	
Operation System	Android9.0
Processor	Qualcomm CPU@ octa-core 1.8 GHz
Memory	RAM: 2 GB ROM: 16 GB
<b>Display System</b>	
Display	5.5" touch screen, 720*1440
<b>Camera</b>	
Pixel	8 MP
<b>Levels</b>	
Tube level	30" / 2 mm
Circular level	8' / 2 mm
<b>Plummet</b>	
Type	Laser Point
Accuracy	1 mm(Instrument Height 1.5 m)
<b>Environmental</b>	
Operating Temperature	-20°C ~ 50°C
Storage Temperature	-40°C ~ 55°C
Temperature and Air Pressure Input	Automatic sensor
Dust&Water Proof (IEC60529 Standard)	IP65
<b>Power Supply<sup>4</sup></b>	
Battery Type	High-energy lithium battery
Voltage/Capacity	7.4V / 6600 mAh
Measuring Times	Approx. 30000 times
<b>Dimension</b>	
Size	206 mm*213 mm*374 mm
Weight	5.75Kg(battery included)

Reminders:

\*1. Good Conditions: good visibility of about 20km, the overcast sky without scintillation.

\*2. Under Kodak white board(90%), measuring distance may vary according to targets and the conditions.

\*3. Measuring time may vary with measuring distance and conditions. For the initial measurement, it may take a longer time.

\*4. Battery life performs best at 25°C. It might be shorter in low temperature or if the battery is old.



AUTHORIZED DISTRIBUTION PARTNER

25M114

**Hi-Target Surveying Instrument Co., Ltd**

ADD: Hi-Target Headquarters, No. 6, Hongchuang 2nd Street, Nancun Town, Panyu District, 511442 Guangzhou, China.  
www.hi-target.com.cn +86-20-28688296 sales@hi-target.com.cn