

iHand55

Professional Field Controller



KEY FEATURES



5.5" sunlight readable display capacitive touch screen for fingers or stylus.



QWERTY full keyboard designed, convenient for different measurement application scenarios.



Equip laser rangefinder(optional) can greatly improve the efficiency of your measurement work.



Android 11 operating system equipped to maintain the productivity of numerous survey projects and data.

TECHNICAL SPECIFICATIONS

Hardware Configuration	OS	Android 11
	Processor	CPU: 8 core; 2.0 GHZ
	Storage	3GB RAM+32GB ROM(Normal version), 4GB RAM+64GB ROM(Laser version); T-Flash memory card, up to 128GB
	Display	720*1440, 5.5", 500 nit, bright Outdoor Color capacitive multi-touch screen (with touch pen, can be operated with gloves)
	Input Configuration	Qwerty full keyboard, number / letter separate, professional custom smart input method
GNSS Features	GNSS	GNSS antenna, GPS, GLONASS, BDS, AGPS
Communication Interface	Network modem	FDD-LTE: B1/B3/B5/B7/B8/B20/B28/B2/B4/B12/B17
		TDD-LTE: B38/B39/B40/B41/B34
		TDSCDMA: B34/B39
		WCDMA: B1/B2/B5/B8/B4
		GSM: B2/B3/B5/B8
		CDMA1x/CDMA2000: BC0
Power Supply	Cellular mobile	4G, Dual Nano-SIM
	WiFi	IEEE 802.11 a/b/g/n/ac, Wapi, AP (2.4G / 5G)
	Bluetooth	BT5.1, BLE, NFC
	USB	USB Type-C interface, OTG, supports fast charging (5V,3A)
Application	Battery	9200mAh lithium-ion battery
	Duration	≥15 hours
	Charging time	4 h (typical)
Physical Features	Camera	Built-in 13 million pixel camera, with laser to replace front camera
	Flash	Highlight Flash LED flash (support flashlight function)
	Sensor	Gravity sensor, compass, light sensor, gyroscope
	Weight	406g (within battery)
	Size	221 mm*78 mm*16.5 mm
	Operating temperature	-30 C ~ +60 C
	Storage temperature	-40 C ~ +80 C
	Humidity	5%-95% non-condensing
	Free fall	1.8 m
Physical Features	Laser ¹	0.6-20m Accuracy: 10mm
		20-40m Accuracy: 30mm
	Shock and vibration	MIL-STD-810H

Descriptions and Specifications are subject to change without notice

1.Suitable for indoor scenes, not suitable for high-precision ranging in strong light environments



AUTHORIZED DISTRIBUTION PARTNER

IP68

25A205

Hi-Target Surveying Instrument Co. Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555, North of Panyu RD, Panyu District, 511400 Guangzhou, China.

www.hi-target.com.cn +86-20-28688296 info@hi-target.com.cn