

TECHNICAL SPECIFICATIONS

Qpad X9		
Configuration	GNSS ¹	Positioning Technology
		GPS, BDS, GALILEO, QZSS
		OS & Processor
		Android 13, 2.7GHz, 8 core high-speed processor
		Storage
		RAM 6GB, ROM 128GB, SD card 1TB
		Display
		8-inch display, touchable screen
		Resolution
		1920×1200, 450nit, readable under the sun
Communication		Camera
		16M pixels rear camera, 8 M pixels front camera, autofocus, highlight LED flash
		Built-in Sensor
		L-sensor (Compatible Design), G-sensor, Gyroscope, E-compass
		USB
		USB 2.0, Type-C, OTG function
		SIM
		Support dual Nano SIM
		Network Type
		5G: FR1 N1/3/20/28/41/77/78/79 FDD: B1/2/3/4/5/7/8/20/28 TDD: B38/39/40/41 3G: B1/B2/B5/B8 GSM:B2/B3/B5/B8
Battery ²		Wi-Fi
		802.11 a/b/g/n/ac (2.4 & 5GHz)
		Bluetooth
		Bluetooth 5.1, BLE
		NFC
		NFC 13.56MHz, work distance ≥ 3cm support ISO/ 14443 A/B, ISO/ 15693, NFC- IP1, NFC-IP2 M1 Card(S50, S70) , CPU Card, NFC Label
		Capacity
		15 hours
		Charging time
		≤ 5 hours
Physical		Size
		236mm*142mm*14mm
		Weight
		636 g (with battery)
		Humidity
		0-95% RH, non-condensing
		Dustproof & Waterproof
		IP67, and 1.2m free drop
		Temperature
		Working: - 20℃ ~ + 60℃; Storage: - 40℃ ~ + 70℃

Descriptions and specifications are subject to change without notice.

1. Optional.

2. The battery operating time is related to the operating environment, operating temperature and battery life.



AUTHORIZED DISTRIBUTION PARTNER

22S102

Hi-Target Surveying Instrument Co. Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555,
North of Panyu RD, Panyu District, 511400 Guangzhou, China.

www.hi-target.com.cn +86-20-28688296 info@hi-target.com.cn

CE IP67

